



# Medrx CAM features and specifications:

- BF Type camera
- Sensor . . . . . CCD 1/4" high sensitivity
- Resolution of the sensor . . . . . (752 x 582) PAL  
. . . . . (768 x 494) NTSC
- Definition . . . . . 470 lines
- Sensitivity . . . . . .2 lux
- Signal/Noise Ratio . . . . . .52 dB
- Electronic shutter . . Automatic (1/50 to 1/100 000)
- Variable surface of analyze for the shutter
- Automatic white balance
- Video enhancement "SHARPNESS"
- Electronic anti-moire filter for flexible fiberscope
- Adjustments of the video parameters
- Automatic detection of the color temperature according to the used light source
- Automatic saving of the adjustments parameters
- 2 programmable buttons
- Cable length . . . . . .3 meters, Ø:5 mm
- 1 USB 2.0 output
- Power supply . . . . . .5 V DC
- Power consumption . . . . . .2.5 VA

## Features of the camera head

- ABS-PC waterproof camera head
- CS-Mount made of aluminium
- Size of the sensor . . . . . L = 87mm; Ø = 30 mm
- Weight of the sensor . . . . . .210g

## Deluxe Probe

- Field of view 60 degree + 10-5 degree
- Focal plane from tip .25" (+/- .125")
- 360 degree glass fiber light at tip
- Conventional optical elements, color corrected
- Minimum intensity 750 FC at 1"
- Working length 1.125" from shoulder
- Tip diameter .120"
- Tapered tip
- Stainless steel body
- Serialized
- Integral glare reduction filter
- 50 grams total weight
- Normal erect image orientation
- Overall length 3.22"
- Body diameter .7"
- Maximum diameter 1.225" dia.
- Swivel mount
- FFA.OS fiber optic socket
- CS mount
- Impervious to alcohol cleaning

## Battery Powered LED Light Source

- 1.25 watt White LED
- 3 AAA, Ni M-H Batteries
- Battery Charger with 3 spare batteries
- Stainless/Aluminum Housing with On/Off Switch

## Video Companion

- RCA (Composite) / S-Video inputs
- Integrated USB 2.0 Cable with internal Capture Device
- Maximum Resolution 720 X 480 (NTSC)
- NTSC / PAL / SECAM capable

## Video Camera

- **Specifications :** Image Sensor: 1/3" Color Interline Transfer CCD
- **Scanning System:** 2:1 Interlace
- **Effective Picture Element:** NTSC: 768 (H) x 494 (V)
- **Horizontal Resolution:** 480 TV Lines
- **Horizontal Frequency:** 15.734 kHz
- **Vertical Frequency:** 59.94 Hz
- **Sync System:** Internal
- **Minimum Illumination:** 0.17 Lux @ F1.2, 50 IRE (AGC On)
- **Gamma:** 0.45
- **DSP:** 10-Bit DSP
- **White Balance:** push to set
- **Mirror Function:** Normal/Mirror Selectable via DSP
- **Serial Port:** RS-232C Serial I/O Port
- **Electronic Shutter:** 1/60 NTSC to 1/100,000 Second
- **Fixed Shutter:** 1/60 Second
- **Flicker Compensation Mode:** On/Off via DSP
- **Electronic Iris:** 1/60 (1/50) to 1/100,000 Second
- **Back Light:** On/Off via DSP
- **Lenses:** CS Mount Lens Mount
- **Video Out:** Composite Video or Y/C Out
- **Power Supply:** 12V DC
- **Power Consumption:** 150mA
- **Operating Temperature:** -10°C ~ 45°C (14°F ~ 113°F)
- **Storage Temperature:** -30°C ~ 60 °C (-22°F ~ 140°F)
- **Weight:** 65g ( 2.29 oz.)
- **Dimensions:** 36 (W) x 36 (H) x 37.35 (D) mm (1.44" x 1.44" x 1.49 ")

Distributed by



1/10 Dorsey Street, Milton QLD 4064, Brisbane, Australia  
Free call: 1800 639 263 Fax 07 3368 1044  
Email: [enquiries@sonici.com.au](mailto:enquiries@sonici.com.au)  
Website: [www.sonici.com.au](http://www.sonici.com.au)